FPPF * YEAR-ROUND TREATMENT TO INCREASE MILEAGE, REDUCE WEAR, REMOVE WATER AND STABILIZE FUEL

FUEL POUER® TOTALLY REMOVES WATER

Diesel fuel contains water year-round. Water damages injectors, scores pintles, abrades fuel pumps, interferes with combustion, fouls injector tips, and creates gum and varnish. Fuel Power contains highly effective ingredients to remove water from fuel. Fuel Power prevents damage, wear, and premature failure.

Regular use of Fuel Power dissolves gum and varnish, cleans injector tips, and restores proper injector spray pattern. The result is improved combustion efficiency, added power, and increased miles per gallon that repay Fuel Power's cost many times over.


Water harbors fungi and microbes. These "bugs" create slime that clogs fuel filters. Fuel Power removes the water in which they live and grow.

Fuel Power reduces oxidation and stabilizes fuel. Fuel Power contains no harmful alcohols to attack your gaskets and seals. Concentrated formula. One 8 ounce bottle treats 240 gallons.

Product Benefits

- Totally disperses water
- Cleans injectors
- Recommended for ULSD and Biodiesel
- Recommended for both common rail and traditional injector systems
- Helps stabilize fuel
- Reduces corrosion of fuel tanks & fuel storage tanks
- Prevents formation of acids
- Safe to double-dose or tripledose for extreme conditions

"FPPF prides itself as the technology leader in the fuel additive business. For over 25 years we have set the standard for quality performance and value. We will continue to provide our customers a superior line of products."





For use in Diesel Fuel, Home Heating Oil, Kerosene, Bunker Fuel and Gasoline




FPPF CHEMICAL COMPANY, INC.

1-800-735-3773

The Premium

Fuel Additive

Company



FUEL POWER™

For use in Diesel Fuel, Home Heating Oil, Kerosene, Bunker Fuel and Gasoline



dirty injector nozzles and restores proper spray pattern by removing carbon, gum and varnish deposits.



FUEL POWER prevents premature wear on hightolerance injector tip needles.



Fuel treated with FUEL POWER

FUEL POWER removes water, "cleans" fuel, and keeps fuel fresh.

For more information consult the Material Safety Data Sheet for this product. All used and unused products should be disposed of in accordance with local, state and federal regulations.

DIRECTIONS:

Add prior to filling for best mixing results. Eight ounces to 240 gallons of diesel fuel keeps injectors clean. Use eight ounces to 125 gallons for first two applications. Use eight ounces to 125 gallons in marine or other extremely wet conditions.

In very cold weather use FPPF Polar Power or FPPF Total Power to prevent icing and gelling of diesel fuel.

Size	Treats	Qty/Case	Stock #
8 ounce bottle	up to 240 gallons	24/case	90100
1 gallon jug	up to 3,840 gallons	4	90101
5 gallon pail	up to 19,200 gallons	1	00102P
55 gallon drum	up to 211,200 gallons	1	00103
	8 ounce bottle 1 gallon jug 5 gallon pail	8 ounce bottleup to 240 gallons1 gallon jugup to 3,840 gallons5 gallon pailup to 19,200 gallons	8 ounce bottleup to 240 gallons24/case1 gallon jugup to 3,840 gallons45 gallon pailup to 19,200 gallons1

Made in U.S.A.

DISTRIBUTED BY:	



FPPF CHEMICAL COMPANY, INC. 117 WEST TUPPER STREET BUFFALO, NEW YORK 14201



FAX: (716) 856-0750 E-MAIL: sales@fppf.com WEBSITE: www.fppf.com

