



The Ultimate Year-Round Diesel Fuel Treatment

TOTAL POWER™

WITH ANTIGEL, MILEAGE IMPROVERS, LUBRICITY, CETANE IMPROVERS, WATER ELIMINATOR, INJECTOR CLEANER, AND FUEL STABILIZER

Total Power is an all-in-one diesel fuel treatment for top performance year-round. It removes water to help prevent bacterial growth. It contains fuel mileage improvers and cetane boosters to reduce fuel costs. Total Power also stabilizes fuel to slow down fuel aging and prevent thermal and oxidation fuel related problems. Total Power does all this while cleaning injectors and preventing fuel gelling in cold temperatures.

Low-sulfur fuels are less lubricating and are more abrasive to delicate engine components. Total Power adds lubricity to prevent pump and engine wear. Total Power also adds cetane improvers and injector cleaner to make starts easier, and improve engine performance.



The Premium Fuel Additive Company

FPPF CHEMICAL COMPANY, INC.



Specifically formulated for use in all diesel engines year-round


MADE IN  THE USA

TOTAL POWER

Product Data Sheet



Before



After

TOTAL POWER cleans dirty injectors and removes gum and varnish deposits.



- Contains Pour Point Depressant
- Lowers Cold Filter Plug Point
- Helps Eliminate Water in Fuel
- Contains Lubricity Additive
- Meets BOCLE Test Standards
- Contains Cetane Improver

- Contains Injector Cleaner & Detergent
- Meets Cummins L-10
- Improves Fuel Economy 4.6% - 14.7%
- Contains Corrosion Inhibitor (N-14 Superior)
- Helps Stabilize Fuel

For more information consult the Material Safety Data Sheet for this product. All used and unused products should be disposed of in accordance with local, state and federal regulations.

DIRECTIONS: Add prior to filling for best mixing results.

TREAT AS FOLLOWS WHEN SUB-FREEZING WEATHER IS PREDICTED:

- One quart added to 250 gallons can lower the Pour Point -30°F and the Cold Filter Plug Point -15°F.
- One quart added to 125 gallons can lower the Pour Point -45°F and the Cold Filter Plug Point -25°F.

TREAT AS FOLLOWS FOR INJECTOR CLEANING:

- One quart to 250 gallons keeps injectors clean.
- One quart to 125 gallons cleans the injectors to L-10 Superior and exceeds N-14 specifications.

The above cold-weather treatment ratios are results for typical fuels. Do not exceed treatment ratio of 1:300 (one quart to 75 gallons). Do not add to gelled fuel. If fuel is already gelled, treat first with *FPPF Melt Down*.

Packaging:

Size	Treats	Qty/Case	Stock #
12 ounce bottle	up to 60 gallons	12/case	90317
32 ounce bottle	up to 250 gallons	12/case	90343
5 gallon pail	up to 5,000 gallons	1	00344P
55 gallon drum	up to 55,000 gallons	1	00345

DISTRIBUTED BY:



FPPF CHEMICAL COMPANY, INC.

117 WEST TUPPER STREET
BUFFALO, NEW YORK 14201

TEL: (716) 856-9607

1-800-735-3773

FAX: (716) 856-0750

E-MAIL: sales@fppf.com

WEBSITE: www.fppf.com

