

**advanced FLOW engineering**

**Instruction Manual** P/N: 46-70380 / 46-70382

**Make: Ford Model: Super Duty F-350/F-450 Year: 2017 Engine: V8-6.7L Power Stroke  
Fits: DANA M300 (14 Bolt) Dual Rear Wheel Axles Only!**



- Please read the entire instruction manual before proceeding.
- Ensure all components listed are present.
- If you are missing any of the components, call customer support at 951-493-7100.
- Ensure you have all necessary tools before proceeding.
- Do not attempt to work on your vehicle when the engine is hot.
- Disconnect the negative battery terminal before proceeding.
- Retain factory parts for future use.

Label	Qty.	Description	Part Number
A1	1	Diff. Cover - Black, Machined Fins; Pro Series (46-70382)	05-60800B
A2	1	Diff. Cover - Raw, Machined Fins (46-70380)	05-60800A
B	1	Porthole View Gauge (Included in 46-70382)	03-50224
C	1	Plug, 3/4" -14 NPTF, 6" Deep Reach	03-50223
D	14	Socket Head Cap Screws, M10 x 1.5 x 30	03-50533
E	1	Plug, Hex Head Socket, 1/8" - 27 NPT (Zn Plt)	03-50029
F	13	Washer, Flat: 3/8"	03-50230
G	1	Plug, 1"-11.5 NPT (included in kit 46-70380)	03-50390
H	1	Plug, M12 x 1.25	03-50385
I	1	Washer, Aluminum: M12	03-50384
J	1	RTV Silicone, Black	05-60096
K	1	Washer, Aluminum: M10	03-50567

Installation will require the following tools:

Oil Drain Pan, 3/8" Drive Ratchet, 12-Point 13mm Socket, 3/16" Allen Wrench, Gasket Scraper, 10mm Socket, 3/8" Torque Wrench, 1/2" Torque Wrench, 8mm Allen Socket, 14mm Socket, 1/2" Drive Ratchet.

**Attention:**

The aFe differential cover is designed to fit the factory axle supplied as original equipment. For some applications or due to the use of certain factory options and/or aftermarket products, there may be clearance issues with the aFe differential cover and other vehicle systems.

It is the responsibility of the installer/vehicle owner to ensure that no other vehicle component come in contact with the aFe differential cover. Contact with any other vehicle component, or any modifications made to the aFe differential cover will automatically void the warranty. aFe assumes no liability, express or implied, for damage or injury to persons or property.

A1



B



C



D



G



K



E



F



I

H



A2



J



REMOVAL

Figure A

**Refer to Figure A for steps 1-3**

Step 1: Park your truck on level ground and apply the parking brake.

Step 2: Position a drain pan under the differential cover.

Step 3: Using a 10mm socket with 3/8" drive ratchet, remove the bolt securing the brake line bracket to the top of the differential housing.


**Figure B****Refer to Figure B for steps 4-6**

Step 4: Using a 12-point 13mm socket with 3/8" drive ratchet, remove the lower 13 bolts on the differential cover. Oil will drain from the lowest bolt hole. Retain the Axle ID tag.

Step 5: Loosen but do not remove the upper most cover bolt.

Step 6: Use a gasket scraper to loosen the cover from the axle housing.



**Figure C****Refer to Figure C for steps 7-9**

Step 7: Remove the upper bolt and cover. Allow the last of the old gear oil to drain.

Step 8: Using a clean, lint free rag, wipe down the remaining oil from the housing. Scrape off old sealant from the sealing surface. This surface must be clean for the new cover to seal.

Step 9: Before installing the aFe differential cover, check the surface of the differential housing for any irregularities. Should there be any, carefully remove any high spots using a smooth flat file.

**DO NOT "ROUND OFF" THE SEALING SURFACE!**



**Figure D**

**Refer to Figure D for steps 10-12**

Step 10: Apply Teflon tape on the threads of all the plug components before installing.

Step 11: Install the M12 magnetic drain plug and washer into the bottom of the aFe differential cover and tighten.

**When installing kit number 46-70380 only:**

Step 12: Install the large 1" NPT plug into the large hole on the side of the differential cover (not shown).

**NOTE: Do not overtighten NPT plugs.**



Figure E

**Refer to Figure E for step 13**

Step 13: Using the silicone provided, lay a continuous bead around the cover.






Figure F

**Refer to Figure F for step 14**

Step 14: Install the aFe front differential cover by aligning the bolt holes and start one of the new 30mm socket head cap screws and washers in the top bolt hole. Continue counterclockwise around the bolt pattern until 12 screws and washers are installed and finger tight. Install the M10 aluminum washer under the bolt to the right of the drain plug. (Circled in Figure F)



Figure G

**Refer to Figure G for steps 15-17**

Step 15: Use the last two socket head cap screws to secure the axle tag at the top of the cover.

Step 16: Using a 8mm hex bit and a 3/8 drive torque wrench, torque the socket head cap screws to 20 - 22 ft.-lbs. in a cross tight pattern.

Step 17: Using the bolt removed in step 3 attach the brake line bracket to the top of the axle housing

INSTALL



Figure H

**Refer to Figure H for step 18**

Step 18: Fill the aFe differential cover using new oil. Fill until the oil runs out of the 1/8" NPT plug of the side of the differential cover.



**Refer to Figure I for steps 19-20**

Step 19: Install the 1/8" NPT plug in the side of the aFe differential cover and wipe off excess oil.

**NOTE: If your vehicle has been modified or lifted and your axle is rotated, you will need to check if you have the correct level of oil in the differential for your vehicle.**

Step 20: Install the 3/4" NPT 6" deep reach magnet into the top of the aFe differential cover and tighten.






Figure J

**Refer to Figure J for step 21**

Step 21: Your installation is now complete.

**NOTE: Retighten all connections after approximately 100-200 miles.**



Momentum Intake System



P/N: 50-73006 (P10R)  
51-73006 (PDS)

Dynamic Air Scoop



P/N: 54-73006-S (For Intake)

SCORCHER HD Module



P/N: 77-43020

Sprint Booster V3



P/N: 77-13001

5" DP-Back Exhaust



P/N: 49-03093 (No Tip)

4" DPF-Back Exhaust



P/N: 49-43092-B (Blk Tips)  
49-43092-P (Pol Tips)

5" DPF-Back Exhaust



P/N: 49-43090-B (Blk Tip)  
49-43090-P (Pol Tip)

Oil Filter



P/N: 44-LF024

Fuel Filter



P/N: 44-FF014

Rear Differential Cover



P/N: 46-70022-WL (w/ Oil)  
46-70020 (RAW)

Oil Cap



P/N: 79-12006

OE Filter Replacement



P/N: 10-10139 (P5R)  
11-10139 (PDS)

To purchase any of the items above, view airflow charts, dyno graphs, photos, and video; please go to [aFepower.com](http://aFepower.com).


# Warranty

## General Terms:

- aFe warrants their products to be free from manufacturer's defects due to workmanship and material.
- This warranty applies only to the original purchaser of the product and is non-transferrable.
- Proof of purchase of the aFe product is required for all warranty claims.
- Warranty is valid provided aFe instructions for installation and/or cleaning were properly followed.
- Proper maintenance with regular inspections of product is required to insure warranty coverage.
- Damage due to improper installation, abuse, unauthorized repair or alteration is not warranted.
- Incidental or consequential damages or cost, including installation and removal of part, incurred due to failure of aFe product is not covered under this warranty.
- All warranty is limited to the repair and/or replacement of the aFe part. To request Return Goods Authorization ("RGA"), email [RGA@afepower.com](mailto:RGA@afepower.com) or call (951)493-7100. Upon receipt of the RGA, you must return the product to the address provided in the RGA, freight prepaid and accompanied with a dated proof of purchase and the RGA. Upon receipt of the defective product and upon verification of proof of purchase, aFe will either repair or replace the defective product within a reasonable time, not to exceed thirty days.

<b>Product Category</b>	<b>P/N Prefix</b>	<b>Warranty duration</b>
Direct OE Replacement Filters	10, 11, 30, 31, 71, 73	Life of the vehicle
Racing Filters	18	1 year
Universal	21, 24, 72	2 years
Air Intake Systems	50, 51, 54, 55, 75	2 years
Exhaust Systems	49	2 years
Intercoolers & Intercooler Tubes	46-2	2 years
Intake Manifolds	46-1	2 years
Differential Cover/Transmission Pan	46-7	Life of the vehicle
Exhaust Manifolds	46	2 years
Throttle Body Spacers	46-3	2 years
Fluid Filters	44	90 days
Pre-Filters	28	2 years
Heavy Duty OE Replacement	70	2 years
PowerSports OE Replacement	81, 87	2 years
PowerSports Intake Systems	85	2 years

No other warranty expressed or implied applies nor is any person or advanced FLOW engineering authorized to assume any other warranty. Some States do not allow the exclusion or limitation of incidental or consequential damages or do not allow limitations on how long an implied warranty lasts, so the above limitations or exclusions may not apply to you. This warranty gives you specific legal rights, and you may also have other rights which vary from State to State.



**advanced FLOW engineering, inc.**

252 Granite Street Corona, CA 92879

TEL: 951.493.7100 • TECH: 951.493.7100 x23

E-Mail: [Tech@aFepower.com](mailto:Tech@aFepower.com)