

INSTALLATION INSTRUCTIONS



1. Remove existing hook/shackle from rope loop.



2. Place rope loop in the cavity of insert. Use insert marked "R" when using synthetic rope, or "C" when using steel cable.



3. Apply two drops of lubricant to insert and spread evenly. Slip rope loop and insert into shackle mount cavity.



4. Secure the insert completely within the cavity.



5. Align rope loop, shackle eyelet, and shackle mount hole.



6. Thread shackle pin through rope loop, shackle eyelet, and shackle mount hole. Secure shackle as per normal operation.



7. Allow approximately 20 minutes for lubricant to dry before pulling shackle mount tight against fairlead.

*Shackle is not required to stow the shackle mount.

REMOVAL INSTRUCTIONS



1. Remove shackle as per normal operation.



2. Grip shackle mount near edges aligned next to the bump off tabs. Without gripping the insert, gradually pull away from the shackle mount and insert.

WARRANTY

Mile Marker warrants directly to the first purchaser that Mile Marker Winch Shackle Mount will be free from defect in material and workmanship appearing under normal use and service for a period of 1 year. Warranty registration must be submitted at milemarker.com/warranty within 30 days. If you discover a hidden defect, Mile Marker will, as its option, repair or replace the product or necessary replacement parts at no charge to you, provided you remove the product from the vehicle and return it prepaid to Mile Marker Industries. If the product was purchased in the United States, the owner must contact our warranty department to get a Return Goods Authorization (RGA) number before returning the product. If the product was purchased outside of the United States, the owner must return the product to the original place of purchase.