



# WEIGH SAFE PINTLE HITCH INSTRUCTION SHEET



## STEP 1

ENSURE THAT YOU ARE USING THE **WEIGH PINTLE ATTACHMENT (C)** WITH A **STEEL WEIGH SAFE DROP HITCH**. **DO NOT USE THE PINTLE ATTACHMENT WITH ANY OF OUR ALUMINUM PRODUCTS.**



## STEP 2

INSERT THE **WEIGH SAFE PINTLE ATTACHEMENT (C)** INTO THE **STEEL WEIGH SAFE SLIDER (B)**. ENSURE THE **STEEL WEIGH SAFE HITCH BALL PIN (A)** IS INSERTED FULLY INTO THE SLIDER. **DO NOT OPERATE WITHOUT STEEL WEIGH SAFE HITCH BALL PIN (A) IN PLACE.**



## STEP 3

PLACE THE **STEEL WEIGH SAFE SLIDER (B)** AT THE DESIRED DROP ON THE **STEEL DRAW BAR (D)** TO ENSURE THAT YOUR VEHICLE AND TRAILER ARE PROPERLY POSITIONED.



## STEP 4

INSERT THE **STEEL DUAL PIN KEY LOCK ASSEMBLY (F)** INTO THE **STEEL WEIGH SAFE SLIDER (B)** AND LOCK IN PLACE BY TURNING THE KEY. **PULL** ON THE **STEEL DUAL PIN KEY LOCK ASSEMBLY (F)** TO ENSURE THAT THE LOCK HAS SECURELY ENGAGED AND PLACE THE **DUST LOCK COVER (E)** OVER THE LOCK. **DO NOT OPERATE WITHOUT MAKING SURE THE KEY LOCK ASSEMBLY (F) IS SECURELY LOCKED IN PLACE.**



## ! IMPORTANT SAFETY INFORMATION !

Ensure safety chains are attached between vehicle & trailer. **DO NOT** attach chains directly to hitch. Never exceed the **LOWER** rating between: A) tow vehicle manufacturer's load **OR** B) Weigh Safe Hitch GTW hitch ratings: 12,500 lbs (Pintle Attachment & 2" shank), 18,500 lbs (Pintle Attachment & 2.5" shank). Tongue weight should be between 10-15% of gross trailer weight. Weigh Safe Hitch max tongue weight is 1,500 lbs (2" shank) and 2,200 lbs (2.5" & 3" shanks). Secure your Weigh Safe Hitch to a standard 2", 2.5", or 3" receiver with locking pin. **DO NOT** use the Pintle Hitch Attachment in the rise position **OR** with any of our aluminum products.



**SCAN  
FOR  
VIDEO**